BRISE

FARO-108H



Product specification

INTERIOR TRACK LIGHT				
Cut out	-			
Dimension	D=Ø108 x H= 181mm	. Ø108 · 158 ·		

Technical description				
Article number	1519.214			
LED Consumption	39.1W			
Current	1050mA			
сст	2700K	3000K	4000K	
Lumen *1	3903lm	4058lm	4121lm	
Øsystem ^{*3}	-	-	-	
Voltage	37.3V			
Reflector	12°/24°/40°			
CRI	90+			
Driver	Remoted, I/P: 90-264V 50/60HZ			
	O/P: 9-48V 1050mA 60w Max			

Photometric

Technical character				
Insulation	CLASS III			
Protection	IP 20			
Tilt	0~90°			
Rotate	0~355°			
Operating temperature	-20~40 °C			
Average Failure Time	L70(10k) >60000 (h)			

Materials				
Luminaire		aluminum die cast		
		-		
Reflector		plastic-PC		
Heat sink		aluminum die cast		
Color available(Body)		white / black / grey		
Color available(Trim ring)		white / black		

Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

Accessories







H11-2 honevcomb louve

Remarks



*1. LUMEN: for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

