ARISE

VELA-80S



Product specification

INTERIOR PENDENT LIGHT				
-	Ø80			
D=Ø80mm x H= 1790mm	1500			
	980			
	Pendent Light -			

Technical description				
Article number	1316.107			
LED Consumption	12.8W			
Current	350mA			
ССТ	2700K	3000K	4000K	
Lumen ^{*1}	1336lm	1387lm	1411lm	
Øsystem ^{*3}	-	-	-	
Voltage	36.5V			
Reflector	40°			
CRI	90+			
Driver	Remoted, I/F	P: 90-264V 50/60	HZ	
Dilvei	O/P: 12-48	O/P: 12-48V 350mA 16w Max		

Photometric

Technical character		
Insulation	CLASS I	
Protection	IP 20	
Tilt	-	
Rotate	-	
Operating temperature	-20~40 °C	
Average Failure Time	L70(6k) >36000 (h)	

Materials		
Luminaire	extruded aluminum	
Reflector	extruded aluminum	
Heat sink	extruded aluminum	
Color available	white / black	
Color available-base	steel	

Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

