## ARISE




## **Product specification**

## **INTERIOR RECESSED DOWN LIGHT**

Ø143mm D=Ø152 x H= 130mm

Ceiling recessed



Technical description					
Article number	1118.191				
LED Consumption	25.5W				
Current	7000mA				
сст	2700K	3000K	4000K		
Lumen <sup>*1</sup>	2565lm	2670lm	2712lm		
Øsystem <sup>*3</sup>	-	-	-		
Voltage	36.5V				
Reflector	20°/40°/60°				
CRI	90+				
Driver	Remoted, I/P : 90-264V 50/60HZ				
	O/P:15-50	O/P: 15-50V 700mA 35w Max			

Technical character		Materials		
Insulation	CLASS I	Luminaire	aluminum die cast body and bezel	
Protection	IP 20		tempered glass	
Tilt	0~70°	Reflector	anodized aluminum	
Rotate	0~355°	Reflector	faceted	
Operating temperature	-20~40 °C	Heat sink	heat conductor pipe	
Average Failure Time	L70(10k) >60000 (h)	Color available	white / black / grey	

#### **Photometric**

# outer box

Package

inner box

#### Accessories

None

#### Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

mm 1 kg

mm 0 kg / 0  $\,$  in 1  $\,$ 

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

I