

ARISE



Product specification





Technical description		
Article number	1268.102	
LED Consumption	3W	
Current	700mA	
сст	2700K	
Lumen ^{*1}	2864~3228lm	
Øsystem ^{*3}		
Voltage	3.5Vdc	
Reflector	15°/36°/48°	
CRI	90+	
Driver	Remoted, I/P 100-240Vac , 50/60HZ	
	O/P: Constant Current 700mA	

Technical character			
Insulation	CLASS III		
Protection	IP 20		
Tilt	0-55°		
Rotate	0-355°		
Operating temperature	-20~40 °C		
Average Failure Time	L70(6k) >36000 (h)		

Materials	
Luminaire	aluminum die cast
Reflector	optic lens
Heat sink	aluminum die cast
Color available	white / black

Package

inner box	mm	kg
outer box	mm	kg / in 1

Stripe Glass

Photometric

Accessories

SG7-1

007 1

Remarks

CE

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.