




ASPHO-180-BH



Product specification

INTERIOR RECESSED DOWN LIGHT	
Installation	Ceiling recessed
Cut out	Ø168mm
Dimension	D=Ø180 x H= 160mm



Technical description

Article number	1418.140		
LED Consumption	62W		
Current	1750mA		
CCT	2700K	3000K	4000K
Lumen *1	7060lm	7553lm	7997lm
Øsystem*3	-	-	-
Voltage	36V		
Reflector	35°		
CRI	90+		
Driver	Remoted, I/P : 90-305V 47/63HZ O/P : 11-257V 75w Max		

Technical character

Insulation	CLASS III
Protection	IP54
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)


Materials

Luminaire	aluminum die cast steel bracket , tempered glass
Reflector	anodized aluminum
Heat sink	forged aluminum
Color available	white / black

Package

inner box	-	mm 1 kg
outer box	-	mm 0 kg / 0 in 1

Photometric



Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.