ARISE

AQUA-90



Product specification

INTERIOR RECESSED DOWN LIGHT				
Installation	Ceiling recessed			
Cut out	Ø85mm	<i>/////</i>		
Dimension	D=Ø90 x H= 112mm	• Ø90 • £		

Technical description				
Article number	1018.128			
LED Consumption	12.8W			
Current	350mA			
ССТ	2700K	3000K	4000K	
Lumen *1	1336lm	1387lm	1411lm	
Øsystem ^{*3}	-	-	-	
Voltage	36.5V			
Reflector	40°			
CRI	90+			
Driver	Remoted, I/F	Remoted, I/P: 90-264V 50/60HZ		
	O/P: 12~48	3 Vdc/350mA,16V	Vatt max.	

Photometric

Technical character		
Insulation	CLASS III	
Protection	IP20	
Tilt	-	
Rotate	-	
Operating temperature	-20~40 °C	
Average Failure Time	L70(10k) >60000 (h)	

Materials			
Luminaire	aluminum die cast		
Reflector	anodized aluminum		
Heat sink	forged aluminum		
Reflector color available	white / black		

Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

Accessories

None

Remarks



- *1. LUMEN: for LED chip test result based on Tc=85°C.
 - This is the ideal (Maximum) lumen. This lumen information is from the LED supplier
- *3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.