




UNI



Product specification

INTERIOR RECESSED DOWN LIGHT	
Installation	Ceiling recessed
Cut out	Ø70mm
Dimension	D=Ø74 x H= 52mm



Technical description

Article number	1418.104		
LED Consumption	8.8W		
Current	250mA		
CCT	2700K	3000K	4000K
Lumen *1	998lm	1036lm	1064lm
Øsystem*3	-	-	-
Voltage	35.1V		
Reflector	20°/40°		
CRI	90+		
Driver	Remoted, I/P : 100-240V 50/60HZ O/P : 250mA Max60V		

Technical character	
Insulation	CLASS III
Protection	IP54
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials	
Luminaire	aluminum die cast
Reflector	plastic-PC
Heat sink	aluminum die cast
Color available	white / black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.