


NEBULA



Product specification

INTERIOR RECESSED DOWN LIGHT

Installation	Ceiling recessed
Cut out	Ø36mm
Dimension	D=Ø41 x H= 37mm

**Technical description**

Article number	1318.112.2BCA
LED Consumption	3W
Current	700mA
Lumen ^{*1}	115lm
Øsystem ^{*3}	-
Voltage	3.5Vdc
Reflector	-
CCT	3000K
CRI	80+
Driver	Remoted, I/P 100-240V AC , 50/60HZ O/P: Constant Current 700mA

Technical character

Insulation	CLASS III
Protection	IP 55
Tilt	-
Rotate	-
Operating temperature	0~35 °C
Average Failure Time	L70(6k) >36000 (h)

Materials

Luminaire	aluminum die cast
Reflector	lens
Heat sink	aluminum die cast
Color available	white / black / chrome / gold / satin

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric**Accessories****Remarks**

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.