


## BUBBLE



## Product specification

**INTERIOR RECESSED DOWN LIGHT**

<b>Installation</b>	Ceiling recessed
<b>Cut out</b>	Ø26mm
<b>Dimension</b>	D=Ø29 x H= 12mm

**Technical description**

<b>Article number</b>	1318.161.2BCA
<b>LED Consumption</b>	1W
<b>Current</b>	350mA
<b>Lumen <sup>*1</sup></b>	95lm
<b>Øsystem <sup>*3</sup></b>	-
<b>Voltage</b>	3V
<b>Reflector</b>	-
<b>CCT</b>	3000K
<b>CRI</b>	80+
<b>Driver</b>	Remoted, I/P: 100V-240V, 50/60HZ, O/P:350mA,

**Technical character**

<b>Insulation</b>	CLASS III
<b>Protection</b>	IP 44
<b>Tilt</b>	-
<b>Rotate</b>	-
<b>Operating temperature</b>	-20~40 °C
<b>Average Failure Time</b>	L70(6k) >36000 (h)

**Materials**

<b>Crystal</b>	lead free optical glass
<b>Heat sink</b>	aluminum
<b>Color available</b>	white / black / chrome / satin nickel

**Package**

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

**Photometric****Accessories****Remarks**

\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture,  
this is the real lumen with the loss because of different design of reflectors and fixtures.