# **URISE**

#### AMIGO-SW-TB3



### **Product specification**

Froduct specification				
INTERIOR COMBO LIGHT				
Installation	Ceiling recessed			
Cut out	☐158x474mm			
Dimension	D=170 485 x H= 152mm	Z Z		
		485		

Technical description				
Article number	1514.405-3			
LED Consumption	25.5W x 3			
Current	700mA			
ССТ	2700K	3000K	4000K	
Lumen *1	2565lm x 3	2670lm x 3	2712lm x 3	
Øsystem <sup>*3</sup>	-	-	-	
Voltage	36.5V			
Reflector	20°/40°			
CRI	90+			
Deiman	Remoted, I/P	: 90-264V 50/60H	Z	
Driver	O/P: 15-50V 700mA 35w Max			

**Photometric** 

Technical character			
Insulation	CLASS III		
Protection	IP 20		
Tilt	0~30°		
Rotate	-		
Operating temperature	-20~40 °C		
Average Failure Time	L70(10k) >60000 (h)		

Materials		
Luminaire	aluminum die cast	
Lummaire	steel housing	
Reflector	anodized aluminum	
Heat sink	forged aluminum	
Color available	white / black	

### Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

# Accessories

None

#### Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

