ARISE

E.



Product specification


INTERIOR COMBO LIGHTInstallationCeilinCut out154

Dimension

□154x316**mm**

Ceiling recessed

D=__145x303 x H= 152mm



Technical description			
Article number	1514.404-2		
LED Consumption	25.5W x 2		
Current	700mA		
ССТ	2700K	3000K	4000K
Lumen ^{*1}	2565lm x 2	2670lm x 2	2712lm x 2
Øsystem ^{*3}	-	-	-
Voltage	36.5V		
Reflector	20°/40°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ		
	O/P: 15-50V 700mA 35w Max		

Technical character		
Insulation	CLASS III	
Protection	IP 20	
Tilt	0~30°	
Rotate	-	
Operating temperature	-20~40 °C	
Average Failure Time	L70(10k) >60000 (h)	

mm 1 kg

mm 0 kg / 0 $\,$ in 1 $\,$

Materials		
Luminaire	aluminum die cast	
Lummane	steel housing	
Reflector	anodized aluminum	
Heat sink	forged aluminum	
Color available	white / black	

Package

inner box outer box Photometric

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

I