# ARISE

### AMIGO-RW-TM1



#### **Product specification**

1 Todact Specification				
INTERIOR RECESSED DOWN LIGHT				
Installation	Ceiling recessed			
Cut out	□86mm	Mir.		
Dimension	D= <u></u> 98 x H= 118mm	98		

Technical description				
Article number	1514.421-1			
LED Consumption	12.8W			
Current	350mA			
ССТ	2700K	3000K	4000K	
Lumen <sup>*1</sup>	1336lm	1387lm	1411lm	
Øsystem <sup>*3</sup>	-	-	-	
Voltage	36.5V			
Reflector	10°/15°/24°/38°			
CRI	90+			
Driver	Remoted, I/P: 90-264V 50/60HZ			
Dilvei	O/P: 12-48V 350mA 16w Max			

**Photometric** 

Technical character				
Insulation	CLASS III			
Protection	IP 20			
Tilt	0~30°			
Rotate	-			
Operating temperature	-20~40 °C			
Average Failure Time	L70(10k) >60000 (h)			

Materials		
Luminaire	aluminum die cast	
Lummane	steel housing	
Reflector	plastic-PC	
Heat sink	forged aluminum	
Color available	white / black	

### Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

## Accessories

None

#### Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

