## **AMIGO-RW-TM3**



# **Product specification**

# **INTERIOR COMBO LIGHT** Ceiling recessed Installation Cut out \_\_86x260mm Dimension D=\_98x272 x H= 118mm 272

Technical description				
Article number	1514.421-3			
LED Consumption	12.8W x 3			
Current	350mA			
ССТ	2700K	3000K	4000K	
Lumen *1	1336lm x 3	1387lm x 3	1411lm x 3	
Øsystem <sup>*3</sup>	-	-	-	
Voltage	36.5V			
Reflector	10°/15°/24°/38°			
CRI	90+			
Driver	Remoted, I/P	Remoted, I/P: 90-264V 50/60HZ		
	O/P: 12-48V 350mA 16w Max			

**Photometric** 

Technical character		
Insulation	CLASS III	
Protection	IP 20	
Tilt	0~30°	
Rotate	-	
Operating temperature	-20~40 °C	
Average Failure Time	L70(10k) >60000 (h)	

Materials		
Luminaire	aluminum die cast	
Lummaire	steel housing	
Reflector	plastic-PC	
Heat sink	forged aluminum	
Color available	white / black	

## **Package**

inner box mm 1 kg  $mm\ 0\ kg\ /\ 0\ in\ 1$ outer box

### **Accessories**

None

### Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

