


KUMA-R-M



Product specification

INTERIOR RECESSED DOWN LIGHT

Installation	Wall recessed
Cut out	Ø74mm
Dimension	D=Ø93 x H= 72mm

**Technical description**

Article number	1495.105
LED Consumption	2.6W
Current	-
CCT	2700K
Lumen *1	140lm
Øsystem*3	-
Voltage	230Vac
Reflector	120°
CRI	80+
Driver	

Technical character

Insulation	CLASS I
Protection	IP 65
Tilt	-
Rotate	-
Operating temperature	-20~35 °C
Average Failure Time	L70(6k) >36000 (h)

Materials

Luminaire	aluminum and steel bracket PC cover
Reflector	None
Heat sink	aluminum die casting
Color available	white / black / brown

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric**Accessories**

Mounting bracket

Recessed can

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

