

## CHAIN-P



## Product specification

INTERIOR PENDENT LIGHT	
<b>Installation</b>	System light
<b>Cut out</b>	
<b>Dimension</b>	573X41X19mm

## Technical description

<b>Article number</b>	1717.103A
<b>LED Consumption</b>	28W
<b>Current</b>	-
<b>CCT</b>	4000K
<b>Lumen *1</b>	-
<b>Øsystem*3</b>	2500 (lm)
<b>Voltage</b>	230V AC
<b>Reflector</b>	120°
<b>CRI</b>	80+
<b>Driver</b>	

## Technical character

<b>Insulation</b>	CLASS II
<b>Protection</b>	IP20
<b>Tilt</b>	-
<b>Rotate</b>	-
<b>Operating temperature</b>	-20~40 °C
<b>Average Failure Time</b>	L70(6k) >36000 (h)


## Materials

<b>Luminaire</b>	steel
<b>Reflector</b>	milky diffuser
<b>Heat sink</b>	
<b>Color available</b>	white

## Package

<b>inner box</b>	mm 1 kg
<b>outer box</b>	mm 0 kg / 0 in 1

## Photometric



## Accessories

None

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.