

## CHAIN-L-H



## Product specification

INTERIOR PENDENT LIGHT	
<b>Installation</b>	System light
<b>Cut out</b>	
<b>Dimension</b>	1147X67X54mm

Technical description	
<b>Article number</b>	1717.105A
<b>LED Consumption</b>	72W
<b>Current</b>	-
<b>CCT</b>	4000K
<b>Lumen *1</b>	-
<b>Øsystem*3</b>	7000 (lm)
<b>Voltage</b>	230V AC
<b>Reflector</b>	30°/60°/90°/Double 20°
<b>CRI</b>	80+
<b>Driver</b>	

Technical character	
<b>Insulation</b>	CLASS II
<b>Protection</b>	IP 20
<b>Tilt</b>	
<b>Rotate</b>	
<b>Operating temperature</b>	-20~40 °C
<b>Average Failure Time</b>	L70(6k) >36000 (h)

Materials	
<b>Luminaire</b>	extruded aluminum
<b>Reflector</b>	optic lens
<b>Heat sink</b>	
<b>Color available</b>	white

Package	
<b>inner box</b>	mm 1 kg
<b>outer box</b>	mm 0 kg / 0 in 1

Photometric

Accessories
None

Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.