ARISE

DEINO



Product specification

	236
8 x H= 164mm	
	¢O]8
	8 x H= 164mm

Technical description			
Article number	1719.202		
LED Consumption	25.9W		
Current	700mA		
ССТ	2700K	3000K	4000K
Lumen ^{*1}	2565lm	2670lm	2712lm
Øsystem ^{*3}	-	-	-
Voltage	37V		
Reflector	18°/26°/38°/55°		
CRI	90+		
Driver	Built in , I/P	: 90-264V 50/60H	Z
	O/P:15-50	V 700mA 35w Ma	ax

Photometric

Technical character		Λ
Insulation	CLASS I	
Protection	IP 20	R
Tilt	0~86°	н
Rotate	0~355°	G
Operating temperature	-20~40 °C	C
Average Failure Time	L70(10k) >60000 (h)	

Materials		
Luminaire	aluminum die cast	
Reflector	plastic-PC	
Heat sink	aluminum die cast	
Gear box	aluminum die cast	
Color available	white / black	

Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

I