ARISE

DEINO

Product specification



INTERIOR COMBO LIGHT

Installation Ceiling recessed

Cut out = 170 x 163mm

Dimension D= 191x191 x H=184mm

Technical description				
Article number	1614.412			
LED Consumption	25.9W			
Current	700mA			
ССТ	2700K	3000K	4000K	
Lumen *1	2565lm	2670lm	2712lm	
Øsystem ^{*3}	-	-	-	
Voltage	37V			
Reflector	18°/26°/38°/55°			
CRI	90+			
Driver	Remoted, I/P: 90-264V 50/60HZ			
	O/P: 15-50V 700mA 35w Max			

Photometric

Technical character			
Insulation	CLASS II		
Protection	IP 20		
Tilt	0~86°		
Rotate	0~355°		
Operating temperature	-20~40°C		
Average Failure Time	L70(10k)>60000(h)		

Materials		
Luminaire	aluminum die cast	
Baffle	plastic-PC	
Reflector	plastic-PC	
Housing	steel	
Heat sink	aluminum die cast	
Color available:	white / black	

Package

inner box - mm 1 kg

outer box - mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

