


DEINO



Product specification

INTERIOR COMBO LIGHT

Installation	Ceiling recessed
Cut out	□=123 x 328mm
Dimension	D=□416x156 x H=130mm

**Technical description**

Article number	1614.415		
LED Consumption	13W X3		
Current	350mA		
CCT	2700K	3000K	4000K
Lumen ^{*1}	1336lmX3	1387lmX3	1411lmX3
Øsystem ^{*3}	-	-	-
Voltage	37.1V		
Reflector	13°/26°/38°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 12-48V 350mA 16w Max		

Technical character

Insulation	CLASS II
Protection	IP 20
Tilt	0~86°
Rotate	0~355°
Operating temperature	-20~40°C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	aluminum die cast
Baffle	plastic-PC
Reflector	plastic-PC
Housing	steel
Heat sink	aluminum die cast
Color available:	white / black

Package

inner box	-	mm	1 kg
outer box	-	mm	0 kg / 0 in 1

Photometric**Accessories**

None

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

