URISE

AMIGO-SW-TLM3



Product specification

INTERIOR COMBO LIGHT				
Cut out	□78x260mm			
Dimension	D=_74x248 x H= 118mm			
		248		

Technical description				
Article number	1514.420-3			
LED Consumption	12.8W x 3			
Current	350mA			
ССТ	2700K	3000K	4000K	
Lumen ^{*1}	1336lm x 3	1387lm x 3	1411lm x 3	
Øsystem ^{*3}	-	-	-	
Voltage	36.5V			
Reflector	20°/40°			
CRI	90+			
Driver	Remoted, I/P: 90-264V 50/60HZ			
	O/P: 12-48V 350mA 16w Max			

Photometric

Technical character		
Insulation	CLASS III	
Protection	IP 20	
Tilt	0~30°	
Rotate	-	
Operating temperature	-20~40 °C	
Average Failure Time	L70(10k) >60000 (h)	

Materials		
Luminaire	aluminum die cast	
Lummane	steel housing	
Trimless recessed frame	steel	
Reflector	plastic-PC	
Heat sink	forged aluminum	
Color available	white / black	

Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

