


## FARO-85V

## Product specification

**INTERIOR TRACK LIGHT**

Installation	Track light
Cut out	-
Dimension	D=Ø85 x H= 147mm

**Technical description**

Article number	1519.215		
LED Consumption	25.5W		
Current	700mA		
CCT	2700K	3000K	4000K
Lumen *1	2565lm	2670lm	2712lm
Øsystem*3	-	-	-
Voltage	36.5V		
Reflector	12°/24°/40°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 15-50V 700mA 35w Max		

**Technical character**

Insulation	CLASS III
Protection	IP 20
Tilt	0~90°
Rotate	0~355°
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

**Materials**

Luminaire	aluminum die cast
Reflector	plastic-PC
Heat sink	aluminum die cast
Gear box	aluminum die cast
Color available(Body)	white / black / grey
Color available(Trim ring)	white / black

**Package**

inner box	-	mm	1 kg
outer box	-	mm	0 kg / 0 in 1

**Photometric****Accessories**

S11-1 snoot  
H11-1 honeycomb louver  
SG11-1 striped glass

**Remarks**

\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

