


RHEA-B



Product specification

INTERIOR RECESSED DOWN LIGHT

Installation	Ceiling recessed
Cut out	Ø104
Dimension	D=Ø117 x H= 104mm

**Technical description**

Article number	1718.142		
LED Consumption	25.5W		
Current	700mA		
CCT	2700K	3000K	4000K
Lumen ^{*1}	2565lm	2670lm	2712lm
Øsystem^{*3}	-	-	-
Voltage	36.5V		
Reflector	12°/24°/40°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 15-50V 700mA 35w Max		

Technical character

Insulation	CLASS II
Protection	IP 44
Tilt	0~30°
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	aluminum die cast
Bezel	aluminum
Reflector	plastic-PC
Heat sink	forged aluminum
Color available: Body/Bezel	black/white

Package

inner box	-	mm	1 kg
outer box	-	mm	0 kg / 0 in 1

Photometric**Accessories**

None

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

