ARISE

MINI-GAGA



Product specification

INTERIOR RECESSED DOWN LIGHT

Installation Cut out

Dimension


∏ IP20

☐ IP65

D=Ø55 x H=63mm

Ceiling recessed

Ø48mm



Technical description		
Article number	1818.143	
LED Consumption	6.4W	
Current	350mA	
сст	2700K 3000K	
Lumen ^{*1}	504 lm 542 lm	
Øsystem ^{*3}	-	
Voltage	18.2V	
Reflector	50°	
CRI	90+	
Driver	Remoted,	
	Output 350mA	

Technical character		
Insulation	CLASS I	
Protection	IP65 (led Module only)	
Tilt	0°~25°	
Rotate	-	
Operating temperature	-20~40 °C	
Average Failure Time	L70(10k)50000(h)	

Materials	
Luminaire	aluminum die cast
	tempered glass
Reflector	plastic-PC
Heat sink	forged aluminum
Color available	white / black

Package

inner box outer box mm 1 kg mm 0 kg / 0 in 1

Photometric

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

- This is the ideal (Maximum) lumen. This lumen information is from the LED supplier
- *3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.